

Growatt SPH3000 / SPH3600 / SPH4000 /
SPH4600 / SPH5000 / SPH6000



With a charge and discharge power of 3KW, the Growatt SPH series is perfect suited to coping with the electricity demand of a private household. As providing the backup power, the household can enjoy an optimum electricity supply even during power outages by adding its accessory (automatic transfer switch). With the Growatt hybrid inverter allowing for both DC- and AC-coupling, the SPH series system is an ideal solution for new installations as well as storage upgrades for existing PV systems.

Leading - edge Technology

User-friendly

- ▶ Local graphic LCD and four buttons, easier for LCD operation
- ▶ USB port for local maintenance and charging cell phone
- ▶ Compact design for easy installation

Reliable

- ▶ IP65 protection degree for indoor and outdoor use
- ▶ Natural cooling, no additional fans
- ▶ Integrated backed-up function, transfer time within 0.5S, automatic transfer switch optional

Flexible

- ▶ Suitable for new and existing solar systems
- ▶ Wide range of PV input power, be more independence from grid
- ▶ Charging and discharging time & power are programmable

Enhanced safety

- ▶ Comprehensive protections: DC reverses polarity protections for PV and battery, etc
- ▶ Flexible charge and discharge mechanism ,reducing impact on the grid
- ▶ Online smart service escort system operation

GROWATT NEW ENERGY TECHNOLOGY Co.,LTD

A: No.28 Guangming Road, Longteng Community, Shiyan, Bao'an District, Shenzhen, P.R.China.

T: + 86 755 2747 1900 F: + 86 755 2749 1460 E: info@ginverter.com

Datasheet	Growatt SPH3000	Growatt SPH3600	Growatt SPH4000	Growatt SPH4600	Growatt SPH5000	Growatt SPH6000
DC input data						
Max. recommended PV power	6600W	6600W	6600W	8000W	8000W	8000W
Start voltage	150V	150V	150V	150V	150V	150V
PV voltage range	120V-550V	120V-550V	120V-550V	120V-550V	120V-550V	120V-550V
MPP voltage range/nominal voltage	150V-550V /360V	150V-550V /360V	150V-550V /360V	150V-550V /360V	150V-550V /360V	150V-550V /360V
Max. input current of tracker A/B	12A/12A	12A/12A	12A/12A	12A/12A	12A/12A	12A/12A
Number of MPP trackers / strings per MPP tracker	2/1	2/1	2/1	2/1	2/1	2/1
AC Output						
Rated AC output power	3000W	3680W	4000W	4600W	4999W	6000W
Max. AC apparent power	3000VA	3680VA	4000VA	4600VA	5000VA	6000VA
Max. output current	16A	16A	22A	22A	22A	27A
Nominal AC output voltage; range	230V ; 180Vac-280Vac	230V ; 180Vac-280Vac	230V ; 180Vac-280Vac	230V ; 180Vac-280Vac	230V ; 180Vac-280Vac	230V ; 180Vac-280Vac
Nominal grid frequency; range	50,50±5Hz	50,50±5Hz	50,50±5Hz	50,50±5Hz	50,50±5Hz	50,50±5Hz
Power factor at rated power	1	1	1	1	1	1
Displacement power factor	0.8leading...0.8lagging	0.8leading...0.8lagging	0.8leading...0.8lagging	0.8leading...0.8lagging	0.8leading...0.8lagging	0.8leading...0.8lagging
THDI	<3%	<3%	<3%	<3%	<3%	<3%
AC output power(Backup)						
Max. output power	3000W	3000W	3000W	3000W	3000W	3000W
Rated AC output voltage	230Vac	230Vac	230Vac	230Vac	230Vac	230Vac
Rated AC output frequency	50Hz	50Hz	50Hz	50Hz	50Hz	50Hz
Automatic switchover time	<0.5S	<0.5S	<0.5S	<0.5S	<0.5S	<0.5S
Battery data						
Battery voltage range	42~59V	42~59V	42~59V	42~59V	42~59V	42~59V
Max. charging voltage	58V	58V	58V	58V	58V	58V
Max charging and discharging current	66A	66A	66A	66A	66A	66A
Max charging and discharging power	3000W	3000W	3000W	3000W	3000W	3000W
Battery type	lithium ion battery/ Lead-acid battery	lithium ion battery/ Lead-acid battery	lithium ion battery/ Lead-acid battery	lithium ion battery/ Lead-acid battery	lithium ion battery/ Lead-acid battery	Lithium-ion /Lead-acid
Deep of discharging	80%DOD/50%DOD	80%DOD/50%DOD	80%DOD/50%DOD	80%DOD/50%DOD	80%DOD/50%DOD	80%DOD/50%DOD
Capacity of battery	3~12kWh	3~12kWh	3~12kWh	3~12kWh	3~12kWh	3~12kWh
Efficiency						
Max. efficiency	97.5%	97.5%	97.5%	97.6%	97.6%	97.7%
Euro European efficiency	97.0%	97.0%	97.0%	97.1%	97.1%	97.1%
MPPT efficiency	99.5%	99.5%	99.5%	99.5%	99.5%	99.5%
Protection devices						
DC switch for each MPPT	yes	yes	yes	yes	yes	yes
DC reverse polarity protection	yes	yes	yes	yes	yes	yes
Battery reverse protection	yes	yes	yes	yes	yes	yes
Output over current protection	yes	yes	yes	yes	yes	yes
Output over voltage protection	yes	yes	yes	yes	yes	yes
Ground fault monitoring	yes	yes	yes	yes	yes	yes
Grid monitoring	yes	yes	yes	yes	yes	yes
Integrated all - pole sensitive leakage	yes	yes	yes	yes	yes	yes
General Data						
Dimensions (W / H / D) mm	547*516*170	547*516*170	547*516*170	547*516*170	547*516*170	547*516*170
Weight	26KG	26KG	26KG	26KG	26KG	26KG
Operating temperature range	-25°C ... +60°C	-25°C ... +60°C	-25°C ... +60°C	-25°C ... +60°C	-25°C ... +60°C	-25°C ... +60°C
Noise emission (typical)	≤ 25 dB(A)	≤ 25 dB(A)	≤ 25 dB(A)	≤ 25 dB(A)	≤ 25 dB(A)	≤ 25 dB(A)
Altitude	2000m	2000m	2000m	2000m	2000m	2000m
Self-Consumption	< 3 W	< 3 W	< 3 W	< 3 W	< 3 W	< 3 W
Inverter Topology	transformerless	transformerless	transformerless	transformerless	transformerless	transformerless
Cooling concept	Natural	Natural	Natural	Natural	Natural	Natural
Environmental Protection Rating	IP65	IP65	IP65	IP65	IP65	IP65
Relative humidity	100%	100%	100%	100%	100%	100%
Features						
DC connection	MC4/H4(opt)	MC4/H4(opt)	MC4/H4(opt)	MC4/H4(opt)	MC4/H4(opt)	MC4/H4(opt)
Interface:RS232/USB/RF/Wi-Fi/LAN	yes /yes /opt/opt/opt	yes /yes /opt/opt/opt	yes /yes /opt/opt/opt	yes /yes /opt/opt/opt	yes /yes /opt/opt/opt	yes /yes /opt/opt/opt
Display	LCD	LCD	LCD	LCD	LCD	LCD
Warranty: 5 years / 10 years	yes /opt	yes /opt	yes /opt	yes /opt	yes /opt	yes /opt
Certificates and Approvals						
CE, IEC62109, G83/G59, VDE0126-1-1, AS4777, AS/NZS 3100, CEI 0-21, VDE-AR-N4105						